SAFETY DATA SHEET



HP 2-C

Section 1. Identification

GHS product identifier : H

Product code : 302011175195

Other means of : Not available.
identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

| Identified uses | |
|----------------------|--------|
| Lubricating Oil | |
| | |
| Uses advised against | Reason |

Supplier's details : Calumet Branded Products, LLC

2780 Waterfront Pkwy E. Drive Suite 200

Indianapolis, IN 46214

USA

Technical Services:317-328-5660

Emergency telephone

number

: 24 hr. CHEMTREC 1-800-424-9300 / International 1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

GHS label elements

Signal word : No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have

product container or label at hand.

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Hazards not otherwise : None known.

classified

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 1/13

HP 2-C

Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Mixture: Not available.

| Ingredient name | % | CAS number |
|---|-----------|------------|
| vistillates (petroleum), hydrotreated heavy paraffinic | ≥25 - ≤50 | 64742-54-7 |
| Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene) | ≥10 - ≤25 | 9003-29-6 |
| Distillates (petroleum), hydrotreated light | ≥10 - ≤25 | 64742-47-8 |
| Isooctadecanoic acid, reaction products with tetraethylenepentamine | ≤3 | 68784-17-8 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ≤2.8 | 64742-65-0 |
| Distillates (petroleum), solvent-dewaxed light paraffinic | ≤2.6 | 64742-56-9 |
| Distillates (petroleum), hydrotreated light paraffinic | ≤2.5 | 64742-55-8 |
| Amine Phosphate Compounds (NJTSR No. 800983-5011P) | ≤0.19 | - |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediate

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in

a fire, symptoms may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 2/13

Section 4. First aid measures

Notes to physician

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 3/13

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational hygiene

- Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|---|---|
| vistillates (petroleum), hydrotreated heavy paraffinic | ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist |
| Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene) | None. |
| Distillates (petroleum), hydrotreated light | ACGIH TLV (United States, 1/2022). [Kerosene as total hydrocarbon vapor] Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours. |
| Isooctadecanoic acid, reaction products with tetraethylenepentamine Distillates (petroleum), solvent-dewaxed heavy paraffinic | None. ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m³ 10 hours. Form: Mist |
| Distillates (petroleum), solvent-dewaxed light paraffinic | STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil |

Section 8. Exposure controls/personal protection

mist, mineral]

TWA: 5 mg/m³ 8 hours.

NIOSH REL (United States, 10/2020). [OIL

MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely

refined]

TWA: 5 mg/m³ 8 hours. Form: Inhalable

fraction

OSHA PEL (United States, 5/2018). [Oil

mist, mineral]

TWA: 5 mg/m³ 8 hours.

NIOSH REL (United States, 10/2020). [OIL

MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist

None.

Distillates (petroleum), hydrotreated light paraffinic

Amine Phosphate Compounds (NJTSR No. 800983-5011P)

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 5/13

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Color : Purple. Odor Odorless. **Odor threshold** : Not available. pH : Not available. **Melting point/freezing point** : Not available. **Boiling point, initial boiling** : Not available.

point, and boiling range

: Closed cup: 126.67°C (260°F) Flash point

: Not available. **Evaporation rate Flammability** : Not available. : Not available. Lower and upper explosion

limit/flammability limit Vapor pressure

Vapor Pressure at 20°C Vapor pressure at 50°C

Ingredient name mm Hg **kPa** Method mm **kPa** Method Hg 1.7 Butene, homopolymer 5.1 0.68 13.05 (products derived from either/or But-1-ene/But-2-ene)

Relative vapor density

: Not available. **Relative density**

0.8549

Solubility(ies)

Media Result cold water Not soluble hot water Not soluble

Solubility in water Partition coefficient: noctanol/water

: Not available. Not applicable.

Auto-ignition temperature

°C °F Ingredient name Method Butene, homopolymer (products 215 419 EU A.15 derived from either/or But-1-ene/But-2-ene)

Decomposition temperature

Not available.

Viscosity

Kinematic (40°C (104°F)): 48.14 mm²/s (48.14 cSt)

Flow time (ISO 2431) : Not available. **Pour point** -54°C (-65.2°F)

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Date of issue/Date of revision 6/13 : 07/31/2023 : 12/14/2022 Version :7 Date of previous issue

Section 10. Stability and reactivity

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|---------|----------------------------|----------|
| istillates (petroleum), hydrotreated heavy paraffinic | LC50 Inhalation Dusts and mists | Rat | 5.7 mg/l | 4 hours |
| Injurous actor floavy paramine | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Butene, homopolymer | LD50 Dermal | Rabbit | >10250 mg/kg | - |
| (products derived from either/ | | | | |
| or But-1-ene/But-2-ene) | | | | |
| | LD50 Oral | Rat | >34600 mg/kg | - |
| Distillates (petroleum), | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| hydrotreated light | | | | |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Isooctadecanoic acid, | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| reaction products with | | | | |
| tetraethylenepentamine | | | _ " | |
| 5 | LD50 Oral | Rat | >5 g/kg | - |
| Distillates (petroleum), | LC50 Inhalation Dusts and mists | Rat | >5.53 mg/l | 4 hours |
| solvent-dewaxed heavy | | | | |
| paraffinic | 1,050,0 | D 11.7 | | |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| Distillator (ostrolous) | LD50 Oral | Rat | >5000 mg/kg | - |
| Distillates (petroleum), | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| solvent-dewaxed light | | | | |
| paraffinic | LD50 Dermal | Rat | >2000 ma/ka | |
| | LD50 Dermai LD50 Oral | | >2000 mg/kg >5000 mg/kg | - |
| Distillator (notroloum) | | Rat | | 4 hours |
| Distillates (petroleum), hydrotreated light paraffinic | LC50 Inhalation Dusts and mists | Rat | >5.53 mg/l | 4 Hours |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Amine Phosphate | LD50 Oral | Rat | 300 mg/kg | - |
| Compounds (NJTSR No. 800983-5011P) | | | | |

Irritation/Corrosion

Not available.

Sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|---------|-------------|
| Mine Phosphate Compounds (NJTSR No. 800983-5011P) | skin | Mouse | Sensitizing |

Mutagenicity

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 7/13

Section 11. Toxicological information

| Product/ingredient name | Test | Experiment | Result |
|--|---|---|----------|
| Amine Phosphate Compounds (NJTSR No. 800983-5011P) | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro Subject: Bacteria | Negative |
| , | OECD | Experiment: In vitro Subject: Mammalian-Animal | Negative |
| | OECD 487 <i>In vitro</i> Micronucleus Test | Experiment: In vitro Subject: Mammalian-Human | Negative |

Carcinogenicity

Not available.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|---|-------------------|-----------|-------------------|---------|-------------------|----------|
| Mine Phosphate Compounds (NJTSR No. 800983-5011P) | - | - | - | Rat | Oral: 75 mg/kg | 28 days |

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Name | Result |
|--|---|
| Distillates (petroleum), hydrotreated heavy paraffinic | ASPIRATION HAZARD - Category 1 |
| Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene) | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), hydrotreated light | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed light paraffinic Distillates (petroleum), hydrotreated light paraffinic | ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 |

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 8/13

Section 11. Toxicological information

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|--------------------|---------|----------|----------|
| Mmine Phosphate Compounds (NJTSR No. 800983-5011P) | Chronic NOAEL Oral | Rat | 75 mg/kg | - |

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/ I) |
|---|------------------|-------------------|--------------------------------|----------------------------------|---|
| ⊮ P 2-C | N/A | 3982.5 | N/A | N/A | N/A |
| Distillates (petroleum), hydrotreated heavy paraffinic | N/A | 2500 | N/A | N/A | 5.7 |
| Distillates (petroleum), hydrotreated light | N/A | 2500 | N/A | N/A | N/A |
| Isooctadecanoic acid, reaction products with tetraethylenepentamine | N/A | 2500 | N/A | N/A | N/A |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | N/A | 2500 | N/A | N/A | N/A |
| Distillates (petroleum), solvent-dewaxed light paraffinic | N/A | 2500 | N/A | N/A | N/A |
| Distillates (petroleum), hydrotreated light paraffinic Amine Phosphate Compounds (NJTSR No. 800983-5011P) | N/A 500 | 2500 1100 | N/A N/A | N/A N/A | N/A N/A |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|-----------------------------------|---------|----------|
| Distillates (petroleum), hydrotreated heavy paraffinic | Acute EC50 >100 mg/l | Algae | 72 hours |
| , | Acute EC50 >100 mg/l | Daphnia | 48 hours |
| | Acute LC50 >100 mg/l | Fish | 96 hours |
| | Chronic NOEL >1 mg/l | Daphnia | 21 days |
| Butene, homopolymer (products derived from either/ or But-1-ene/But-2-ene) | Acute EC50 >1000 mg/l | Daphnia | 48 hours |
| , | Acute LC50 >1000 mg/l | Fish | 96 hours |
| Distillates (petroleum), hydrotreated light | Acute EC50 >1000 mg/l | Algae | 72 hours |
| , | Acute LC50 >1000 mg/l Fresh water | Daphnia | 48 hours |
| Isooctadecanoic acid, reaction products with tetraethylenepentamine | Acute EC50 94 mg/l | Algae | 4 days |
| • | Acute EC50 >1000 mg/l | Daphnia | 2 days |
| | Acute NOEC 23 mg/l | Algae | 4 days |
| | Acute NOEC >10 mg/l | Daphnia | 21 days |

Section 12. Ecological information

| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Acute EC50 >100 mg/l | Algae | 72 hours |
|---|----------------------|---------|----------|
| paramina | Acute EC50 >100 mg/l | Daphnia | 48 hours |
| | Acute LC50 >100 mg/l | Fish | 96 hours |
| | Chronic NOEL >1 mg/l | Daphnia | 21 days |
| Distillates (petroleum), solvent-dewaxed light | Acute LC50 4.5 mg/l | Fish | 96 hours |
| paraffinic | " | | |
| Distillates (petroleum), hydrotreated light paraffinic | Acute EC50 >100 mg/l | Algae | 72 hours |
| | Acute EC50 >100 mg/l | Daphnia | 48 hours |
| | Acute LC50 >100 mg/l | Fish | 96 hours |
| Amine Phosphate Compounds (NJTSR No. 800983-5011P) | Acute EC50 1.9 mg/l | Algae | 72 hours |
| , | Acute EC50 6.8 mg/l | Daphnia | 48 hours |
| | Acute LC50 18 mg/l | Fish | 96 hours |
| | Acute NOEC 0.1 mg/l | Algae | 72 hours |
| | Acute NOEC 3.9 mg/l | Daphnia | 48 hours |
| | Acute NOEC 12 mg/l | Fish | 96 hours |

Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|---|---|-----------------------|------------|------------------|
| Distillates (petroleum), hydrotreated light | OECD 301F Ready Biodegradability - Manometric Respirometry Test | 69 % - Readily - 28 | days - | - |
| Isooctadecanoic acid, reaction products with tetraethylenepentamine | OECD 301B Ready Biodegradability - CO ₂ Evolution Test | 4.5 % - 28 days | - | - |
| Amine Phosphate Compounds (NJTSR No. 800983-5011P) | OECD 301B Ready Biodegradability - CO ₂ Evolution Test | 9 % - Not readily - 2 | 8 days - | - |
| Product/ingredient name | Aquatic half-life | • | Photolysis | Biodegradability |
| Distillates (petroleum), | - | | - | Inherent |

| Product/ingredient name | Aquatic nair-life | Photolysis | Biodegradability |
|----------------------------------|-------------------|------------|------------------|
| D istillates (petroleum), | - | - | Inherent |
| hydrotreated heavy paraffinic | | | |
| Butene, homopolymer | - | - | Not readily |
| (products derived from either/ | | | |
| or But-1-ene/But-2-ene) | | | |
| Distillates (petroleum), | - | - | Readily |
| hydrotreated light | | | |
| Isooctadecanoic acid, | - | - | Not readily |
| reaction products with | | | |
| tetraethylenepentamine | | | |
| Distillates (petroleum), | - | - | Inherent |
| hydrotreated light paraffinic | | | |
| Amine Phosphate | - | - | Not readily |
| Compounds (NJTSR No. | | | |
| 800983-5011P) | | | |

Bioaccumulative potential

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 10/13

HP 2-C

Section 12. Ecological information

| Product/ingredient name | LogPow | BCF | Potential |
|--|------------|-------------|-----------|
| Distillates (petroleum), hydrotreated heavy paraffinic | >6 | - | High |
| Butene, homopolymer (products derived from either/ or But-1-ene/But-2-ene) | 7.6 to 7.8 | 314 to 1882 | High |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 2 to 6 | - | High |
| Distillates (petroleum), hydrotreated light paraffinic | >6 | - | High |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | IMDG | IATA |
|-----------|--------------------|--------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: naphthalene

TSCA 8(a) CDR Exempt/Partial exemption: Not determined TSCA 8(c) calls for record of SAR: trimethyl phosphate

Clean Water Act (CWA) 307: naphthalene Clean Water Act (CWA) 311: naphthalene

Clean Air Act Section 112

(b) Hazardous Air

Listed

Pollutants (HAPs) Clean Air Act Section 602

: Not listed

Class I Substances

Date of issue/Date of revision : 12/14/2022 Version: 7 11/13 : 07/31/2023 Date of previous issue

Section 15. Regulatory information

Clean Air Act Section 602

Class II Substances

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Not applicable. **Composition/information on ingredients**

| Name | % | Classification |
|-----------------------------------|-----------|--------------------------------|
| pistillates (petroleum), | ≥25 - ≤50 | ASPIRATION HAZARD - Category 1 |
| hydrotreated heavy paraffinic | | |
| Butene, homopolymer (products | ≥10 - ≤25 | ASPIRATION HAZARD - Category 1 |
| derived from either/or But-1-ene/ | | |
| But-2-ene) | | |
| Distillates (petroleum), | ≥10 - ≤25 | ASPIRATION HAZARD - Category 1 |
| hydrotreated light | | |
| Isooctadecanoic acid, reaction | ≤3 | SKIN IRRITATION - Category 2 |
| products with | | EYE IRRITATION - Category 2A |
| tetraethylenepentamine | | |
| Distillates (petroleum), solvent- | ≤2.6 | ASPIRATION HAZARD - Category 1 |
| dewaxed light paraffinic | | |
| Distillates (petroleum), | ≤2.5 | ASPIRATION HAZARD - Category 1 |
| hydrotreated light paraffinic | | |

State regulations

Massachusetts : None of the components are listed. **New York** : None of the components are listed. **New Jersey** : None of the components are listed. **Pennsylvania** : None of the components are listed.

California Prop. 65

MARNING: This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Information provided is based on industrial use and may not be relevant to consumer applications.

| Ingredient name | Concentration (%) | No significant risk level | Maximum acceptable dosage level |
|---------------------|-------------------|---------------------------|---------------------------------|
| Naphthalene | 0.061106 | Yes. | - |
| Trimethyl phosphate | 0.001 - 0.002 | Yes. | - |

International lists

National inventory

Australia : All components are listed or exempted. Canada : All components are listed or exempted. China : At least one component is not listed.

Eurasian Economic Union : Russian Federation inventory: Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined. Republic of Korea : Not determined.

HP 2-C

Section 15. Regulatory information

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : All components are active or exempted.

Viet Nam : Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

| Classification | Justification |
|-----------------|---------------|
| Not classified. | |

History

Date of issue/Date of : 07/31/2023

revision

Date of previous issue : 12/14/2022

Version : 7

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 07/31/2023 Date of previous issue : 12/14/2022 Version : 7 13/13